

PRODUCT PHOTO

SPECIFICATION



SD-SD001

Main Material: Quality cold-rolled steel sheet & stainless steel (steel sheet thickness available from 0.5mm~1mm for door panel; 1mm~1.8mm for frame)

Cold-rolled steel door leaf and frame with heat transfer-printing, which looks natural wood grain.

Infills: Honeycomb material or polyurethane or silicic aluminum and anti-fire board material.

The standard Frame outer size (H x W): 2050mm*960(860)mm

Door leaf thickness: 42mm~90mm, Door frame depth: 80mm-280mm.

Opening direction: Left or right; inside or outside open, Lock handle direction: on left/right, Opening degree: 110 degree, 180 degree.

Accessories: specialty multi-point lock, adjustable, reinforced hinges, handles, peephole, hidden doorbell, rubber seal, doorbell, installing bolts

Packing: foam board and foam plastic bag and strong chipboard.

Container capacity: 100~125 pcs/20Ft, 230~256pcs/40Ft, 250~270pcs/40HQ

Applicable for the entrance of houses or flats, Environment friendly paint used



SD-SD002



SD-SD003



SD-SD004



SD-SD005



SD-SD006



SD-SD007



SD-SD008



SD-SD009



SD-SD010



SD-SD011



SD-SD016



SD-SD017



SD-SD018



SD-SD019



SD-SD020



SD-SD021



SD-SD023



SD-SD024



SD-SD025



SD-SD026